

# Yamaha Steinberg USB Driver V1.6.2 for Windows Release Notes

---

## Contents

[System Requirements for Software](#)

[Main Revisions and Enhancements](#)

[Legacy Updates](#)

## System Requirements for Software

### NOTE

Note that the system requirements may be slightly different from those described below depending on the particular operating system.

OS	Windows XP Professional SP3/Windows XP Home Edition SP3(*)/ Windows Vista SP2 (32-bit/64-bit)/ Windows 7 SP0/SP1 (32-bit/64-bit)
CPU	Pentium/Athlon 2GHz or faster (dual core processor recommended)
Memory	1GB or more (2GB or more on Windows 7 64-bit)
Interface	Equipped with a USB 1.1 or 2.0 connector (depends on the device)
Hard Disk	Free disk space of 100MB or more; high-speed hard disk

(\*) Yamaha 01V96i does not support Windows XP Professional SP3 or Windows XP Home Edition SP3.

## Main Revisions and Enhancements

### V1.6.1 to V1.6.2

- Improved the performance.

## Legacy Updates

### V1.6.0 to V1.6.1

- Solved a problem related to computers equipped with certain AMD brand CPUs, in which noise might occur in the audio input signal when using the device with such a computer.

### **V1.5.2 to V1.6.0**

- Now supports Yamaha 01V96i.
- Solved the problem in which the audio input/output might stop when switching the sample rate in the Cubase project setup.
- Solved some other minor problems.

### **V1.5.1 to V1.5.2**

- Solved some minor problems.

### **V1.5.0 to V1.5.1**

- Now supports Steinberg UR824.
- Changed the default buffer size of the ASIO driver from 768 samples to 512 samples.
- Solved some minor problems.

#### **NOTE**

Yamaha Steinberg USB Driver V1.5.1 is the version which is included in the TOOLS for UR824 CD-ROM (labeled "YD307A0" or "YD307B0" ) in the Steinberg UR824 package.

### **V1.3.0 to V1.5.0**

- Now supports Steinberg UR28M.
- Improved the user interface on the control panel of the driver. Tabs are displayed depending on the connected devices.
- Added selections of 64 samples and 96 samples to the buffer size setting of the ASIO driver.

#### **NOTE**

Yamaha Steinberg USB Driver V1.5.0 is the version which is included in the TOOLS for UR28M CD-ROM (labeled "YD304A0" or "YD304B0") in the Steinberg UR28M package.

### **V1.1.2 to V1.3.0**

- Now supports Yamaha MOX6/8.
- Added the function which allows selection of the device using ASIO within the control panel of the Yamaha Steinberg USB Driver.
- Yamaha Steinberg USB Driver has been confirmed to work properly on Windows 7 SP1.
- Changed the system requirements to the following.
  - Windows XP Professional SP3, Windows XP Home Edition SP3, Windows Vista SP2, and Window 7 SP0/SP1

For details, refer to the “[System Requirements for Software](#).”

#### **V1.1.1 to V1.1.2**

- Improved the stability of Yamaha Steinberg USB Driver.

#### **V1.1.0 to V1.1.1**

- Improved the following problem.
  - When using a device compatible with Yamaha Steinberg USB Driver on a computer with an Intel® 5 series chipset, recorded audio data might be briefly interrupted.

#### **V1.0.1 to V1.1.0**

- Now supports Steinberg CI1 and Steinberg CI2+.

#### **V1.0.0 to V1.0.1**

- Yamaha Steinberg USB Driver has been confirmed to work properly on Windows 7.
- Solved a problem in which noise may occur in a certain environment.

---

Company and product names that appear in this document are the trademarks or registered trademarks of their respective companies.

(C) 2010-2012 Yamaha Corporation All Rights Reserved.